



Installing instruction in wall of concret swimming pool with foil coating.

Installation for Tiles 6mm or 8mm.



Installation for Tiles 10mm or 12mm.



Installation in foil coating swimming pool:

Section B-B show section of foil coating swimming pool wall after dismantling of formwork and installation foil coating and tiles. Flange of Basket should be covered by adhesive flange, layer of foil coating, layer of mortar and tiles see detail C. Maximum thickness of Adhesive Flange, Foil Coating, Mortar and Tiles see table Tiles Thickness.

Mikro Led			
Tiles Thickness [mm]	Mortar Thickness [mm]	If additional Washer should be mounted:	Quantity of additional Washer[pcs]
6	6,5	no	0
8	4,5	no	0
10	4,5	yes	1
12	4,5	yes	2

Standard Led			
Tiles Thickness [mm]	Mortar Thickness [mm]	If additional Washer should be mounted:	Quantity of additional Washer[pcs]
6	6,5	no	0
8	4,5	no	0
10	4,5	yes	1
12	4,5	yes	2

Medium Led			
Tiles Thickness [mm]	Mortar Thickness [mm]	If additional Washer should be mounted:	Quantity of additional Washer[pcs]
6	6,5	no	0
8	4,5	no	0
10	4,5	yes	1
12	4,5	yes	2

Big Led			
Tiles Thickness [mm]	Mortar Thickness [mm]	If additional Washer should be mounted:	Quantity of additional Washer[pcs]
6	7,5	no	0
8	5,5	no	0
10	5,5	yes	1
12	5,5	yes	2
16	3,5	yes	3

Dimension type:	Sign	Mikro Led	Standard Led	Medium Led	Big Led
Front Ring diameter:	A	∅ 90mm	∅ 130mm	∅ 178mm	∅ 245mm